



ITALCAR INDUSTRIAL S.r.l. – Via Bruino, 36 – 10040 Rivalta di Torino
tel. 011.9040225 – fax 011.9032986
www.italcar.com - info@italcar.com



MODEL ATTIVA AMBULANCE.4 48 V

TECHNICAL FEATURES – ATTIVA AMBULANCE.4 48V

ENGINE:	DC 48V - ADC	VOLTAGE:	48 volt
BATTERIES:	6 x 8volt mod. US battery 8VGC	SUSPENSION:	front: independent suspension rear: leaf springs with hydraulic shock absorbers
CONTROLLER:	electronic engine SEM Curtis, mod. 1266 with feature walk away	CHASSIS BODY:	galvanized steel frame and powder coated main body: PP impregnated and painted equipped for the transport of injured people
TRANSMISSION:	rear axle, 19 spline, ratio 12,31:1	PERFORMANCES:	* max speed: 30 km/h * range: 80 km. * hill climbing ability: 15%
<small>datas are to be considered indicative and calculated on the average of different conditions of use</small>			
STEERING:	self compensating single reduction rack and pignon	TYRES:	205 / 50 – 10 - aluminium rims
BRAKES:	self-adjusting dual rear wheel mechanical drum brakes	BATTERY CHARGER:	included with the vehicle. 48v, 220/230V
OVERALL DIMENSIONS:	length 2800mm width 1180mm height (max) 2150mm	BASIC CONFIGURATION:	reverse buzzer, digital speedometer, foldable alloy stretcher with security belts, front and rear lights, horn, direction indicators, rear-view mirrors, plexiglass
		COLOURS:	white
		TURNING RADIUS:	3 mt

All data reported are indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice